Packet Switch Service Orders - Interim Procedures

MEMORANDUM

August 13, 1985

The WISCONSIN BELL PACKET SWITCHING NETWORK has been installed and final acceptance tests are underway. The network in its present state is capable of supporting selected official service data applications, however some minor service interruptions may be experienced until the acceptance tests are completed.

The official service data applications that will be incorporated on the packet switch must have a voice or private line circuit access. These services will be installed via our existing service order procedures. In addition the information relating to the packet switch access (Tie Pairs, IPM, Channel Numbers, and other options) will be on the same service order. Presently USOC's and FID's have not been completely defined and validated in the SORD/CRIS system, consequently the packet switch information required for installation will be contained as "DES" and "RMKS" on the order. This method will be used until all the USOC's and FID's are validated.

The service orders will be written by the respective official voice and data BUSINESS OFFICES. Two types of access to the packet switch will be utilized by the official service user, data over voice (DVM) and private line access.

DVM PROCEDURES

The Mechanized Assignment Centers will assign the DVM equipment associated with the packet network from information on the service order. MAC will then generate a frame ticket to the appropriate C.O forces. The central office wiring of the voice lines, and installation and maintenance of the DVM modem's in the data cabinets will be done by Network Switch Services Administration and Maintenance Forces. The Official Services I&M (voice) group will install the voice line, and the associated customer premises modular modem if wiring is required. The Packet Network Control Center will do the software programming associated with the packet switch.

PRIVATE LINE CIRCUITS PROCEDURES

The S&E section of the SORD order will contain information pertaining to the packet switch PAD access port and tie pairs, from the packet switch blocks in the central office to the General Data Comm (GDC) modem cabinet. The private line data circuits will be designed by the CIRCUIT PROVISIONING CENTER (CPC). Network Switch Service, Special Services forces will perform the central office wiring plus install the GDC modem in the cabinet. The private line circuit from the serving C.O to the customers premises will be installed and maintained by Special Services I&M forces. The circuits should use central office padding not 829's.

It is requested that the Special Services I&M technician call the PNCC at 414-678-4420 to inform them of the slot used in the multiple mounting GDC rack. The Packet Network Control Center will do the software programming associated with the packet switch features and options.

The attached exhibits show service order examples and frame work diagrams for connecting the lines and circuits to the packet switch network. If you have additional questions, please contact me at 414-678-3846.

Hon Johnson

Assistant Manager - Packet Switching

Attachment

CC:

Mr. Anauo Mr. Cash

Mr. G.J. Doerr

Mr. R. Hale

Mr. E.W. Hargarten

Mr. Hoida

Mr. Kerber

Mr. Kondracki

Mr. Mathiak

Mr. Meetz

Mr. Mogden

Mr. J. Murphy

Mr. Oliphant

Mr. R.A. Perry

Mr. B. Peterson

Mr. Rothman

Mr. Rucks


Mr. S. Sherman

Mr. T. Sherman

Mr. J. Stern

Mr. Walsh

Mr. Willet



1 PACKET SWITCH CABINET (CONTAINS SEISCOR DVM MULT MOUNTING RACK)

CH = SLOT CDVM CIRCUIT PACKS PLUG INTO MDF EQ= PHYSICAL LOCATION OF DVM BLOCKS DVM = CIRCUIT NUMBER ON THE BLOCKS


DIN = DATA TERMINAL NUMBER

SERVICE ORDER


FORM 7401-37-40-2 (5-83)

	•	,
	5010 OET FICE482131.31/13 101	I
	\$017 CEL FICRARATATE (IR CCC *MSG	
	CII	10 C
		LITN
	EDG SS; CO-SS; FA	LISTA
	F3 1	ACCN
		DIST. CABLE LEAD PAIR
		DIST. CADLE LEAD FAIR
	NIST (SENI)WISCONSINE FELL	DIST. TERM ADDRESS
	16 782 N FROADVAY	DIST. TERM ADDRESS
		STAT
	(1)	
	111 F-6/1111 6-6	/SWO
	/I = ==:/:TI E=11	/NI
	17.7 -22	/RI /RCO
	FTI 6-29	/RF /LIC
	NOON I BRICKETS 678-7808	/LIF /WSR
	¥ 00 1114 ww 07 414 678-7505	/OCB
	606 1318 NO 414 675-0565	/HRS
	000 /CIV 11 414 678-1787	
ļ		/CD
1	843	START COMP TIME TIME
	1018 84.1/17.882883877	LATIS DATA
	109 IICII	WC ID.
	10EI 1-722 ' FRIY	CAPR
	1 11634 DES PACKET SWITCH CAB	LSTWOLBCT
(1)	IPM 2-9 CH 2, MDF TIE PR	CDP PBC CIP
\smile	LS1 S83, DTN 4142749913	RERTC
	, =====================================	SODODFOAC
	I FECCIARS BIN BOY SE HARR	155
	E-MARCHAR MAIL CONN'I	SSNO
	1041 2-74x * FRIY	ERRERR
	1 11604/116 RM 31,	TRANSMISSION/NOISE
		MEASUREMENT
7	DIGUER GUILBOU GIRINDE (GOUELING D.C. DID)	
(1) PACKET SWITCH CABINET (CONTAINS	P.S PAD)
IPM = INTERFACE PANEL MODULE (MOUNTED IN REAR OF		E (MOUNTED IN REAR OF P.S CABINET
	CH = CHANNEL (RS232 NUMBER ON IPM) MDF TIE PR= WIRING LOCATION ON P.S BLOCKS TO GDC EQUIPMENT	
S83 = PHYSICAL LOCATION OF BLOCK DTN = DATA TERMINAL NUMBER		

DVM C.O WIRING





EXISTING VOICE LINE



DVM WIKING TO PACKET SWITCH DATA NETWICKER

PRIVATE LINE CIRCUIT C.O WIRING





PRIVATE LINE CIRCUIT WIRING TO PACKET NETWORK