

1

/FOR

WFADI SECURITY SIGNON/SIGNOFF SCREEN

TO SIGNON: ENTER THE SIGNON NAME AND PASSWORD, THEN PRESS THE "ENTER" KEY.

TO SIGNOFF: ENTER A "Y" IN THE SIGNOFF FIELD, THEN PRESS THE "ENTER" KEY.

SIGNON: p1edb

PASSWORD: P1EDB

SIGNOFF:

EFFECTIVE ZONE NAME:

NOTICE - EXCEPT AS MAY OTHERWISE BE PERMITTED, IN WRITING, BY
BELL COMMUNICATIONS RESEARCH INC. (BELLCORE) ACCESS TO THIS SOFTWARE
IS LIMITED TO ONLY BELLCORE AUTHORIZED LICENSEES AND SUBLICENSEES.

COPYRIGHT 1990 BELLCORE- ALL RIGHTS RESERVED.

SEC000I SIGNON SUCCESSFUL.

OQS CMD: QUERY: LOC DB: PIEOS NEWDB: /FOR
USER: CCC_USER WFADI/OQS REPORTING SCREEN(XOQSRE) 02/15/94 08:07:59
"ESS PLUG SPARES BY CO LOCATION", "INPUT CO CLLI", CST
SELECTION COMPARISONS: SELECTION ENTRIES:
LOC IS ' \$==> 'milwwi16ds0'

OQS600I: REPORT PROCESSING SUCCESSFULLY COMPLETED.

FOR HELP, PRESS PF11

ESS PLUG SPARES BY CO LOCATION

INPUT CO CLLI

REPORT NAME = LOC, DATA BASE =PIE0\$, USER = CCC_USER

LOC IS 'MILWWI16DS0';

WFADI/OQS ===== 02/15/94 08:09:55 CST

LOCATION	TYPE	MCODE/REL	SP#	COMMENT
MILWWI16DS0	NTBX01AA	27	01	
	NTBX01AB	20	01	
	NTBX02AA	44	01	
	NTBX27AA	06	01	
	NTBX34BA	06	01	
	NTBX35BA	32	01	
	NTBX36BA	03	01	
	NTBX71AA	08	01	
	NTBX72AA	02	01	
	NTEX20AA	01	01	
	NTEX20BA	02	01	
	NTEX22AA	08	01	
	NTEX22BB	11	01	
	NTEX25AA	02	01	
	NTEX25BA	02	01	

<PAGE 1 >CONTINUED---PF2=FORWARD,PF6=RETURN TO INPUT SCREEN

DESIRED PAGE

CURRENT PAGE

1

OQS CMD: QUERY: TYPE DB: PIEOS NEWDB: /FOR
USER: CCC_USER WFADI/OQS REPORTING SCREEN(XOQSRE) 02/15/94 08:10:44
"ESS PLUG SPARES BY TYPE. INPUT PLUG-TYPE.", CST
SELECTION COMPARISONS: SELECTION ENTRIES:
TYPE IS ' '; \$==> 'nt6x50ab

OQS600I: REPORT PROCESSING SUCCESSFULLY COMPLETED.

FOR HELP, PRESS PF11

ESS PLUG SPARES BY TYPE. INPUT PLUG-TYPE.

REPORT NAME = TYPE, DATA BASE =PIE03, USER = CCC_USER

TYPE IS 'NT6X50AB';

WFADI/OQS ===== 02/15/94 08:11:38 CST

TYPE	LOCATION	MCODE/REL	SPR #	COMMENT
------	----------	-----------	-------	---------

NT6X50AB	MILWWI16DS0	AF	01	
		AF	02	
		AF	03	
	MILWWI28DS0	AF	01	
	PEWKWI40DS0	AN	01	

SPARE PLUG LOCATIONS BY TYPE, AND NUMBER OF SPARES AT LOC

<PAGE 1 >END
 DESIRED PAGE

---PF6=RETURN TO INPUT SCREEN

CURRENT PAGE 1

QOS CMD: res QUERY: PIE DB: PIE05 NEWDB: /FOR
USER: CCC_USER WFADI/QOS REPORTING SCREEN(XOQSRE) 02/15/94 08:13:34
"PLUG IN EQUIPMENT BY LOC, TYPE, HECIG" CST
SELECTION COMPARISONS: SELECTION ENTRIES:

QOS770I: DEFAULT SETTINGS HAVE BEEN USED

FOR HELP, PRESS PF11

COMMAND: MANAGERS SCRATCH PAD DATA EDITOR (XMSPDE)
USER : CCC_USER DB: PIE05 DESC: *PROC GENERATED DB*
DATA AS OF: 02/11/94 15:47:37

/FOR
02/15/94 CST
08:20:48

FIELD	LEN	DATA
LOC	11	milwwi16ds0
TYPE	15	nt6x50ab
SPARE#	3	01
MCODE_REL	11	
HECI	10	
COMMENT	76	

DESIRED PAGE .
MSP100I: FIND SUCCESSFUL

PAGE 1
FOR HELP, PRESS PF11

7

COMMAND: MANAGERS SCRATCH PAD DATA EDITOR (XMSPDE) /FOR
USER : CCC_USER DB: PIE 05 DESC: *PROC GENERATED DB* 11/11/93 SYS
DATA AS OF: 11/11/93 08:55:17 11:34:55

FIELD	LEN	DATA
LOC	11	SUSXWI46DS0
TYPE	15	NT2T10BB
SPARE#	3	01
MCODE_REL	11	F
HECI	10	EMPQNOM1AA
COMMENT	76	repair 08-11-93

DESIRED PAGE .
MSP100I: FIND SUCCESSFUL

PAGE 1
FOR HELP, PRESS PF11

8

COMMAND: MANAGERS SCRATCH PAD DATA EDITOR (XMSPDE)
USER : CCC_USER DB: PIE03 DESC: *PROC GENERATED DB*
DATA AS OF: 11/11/93 08:55:17

/FOR
11/11/93 SYS
11:37:52

FIELD	LEN	DATA
LOC	11	WTTNWI01DS0
TYPE	15	TN269
SPARE*	3	01
MCODE_REL	11	MC5D014A1
HECI	10	ESMQ014
COMMENT	76	

DESIRED PAGE .
MSP100I: FIND SUCCESSFUL

PAGE 1
FOR HELP, PRESS PF11