



DESCRIPTION

The DRT1183C provides a compact, yet powerful, collection capability against Push-to-Talk (PTT) signals. The system is based on an industry-standard bus format, and uses the latest digital signal processing (DSP), RF, and microprocessor technology. The DRT1183C supports a full complement of third generation modules.

- Monitors up to 336 half-duplex channels (up to 48 channels per WPM3A).
- Software configurable.
- DF option available.
- Flexible tuner configuration provides frequency coverage of all bands of interest.
 - RFT3A-40 (Standard): Dual channel receiver VHF/UHF coverage from 20 – 3000 MHz; HF from 0.5 – 32 MHz
 - RFT4 (Optional): Dual channel transceiver VHF/UHF coverage from 20 – 6500 MHz; HF from 0.5 – 32 MHz
 - HFT1B (Optional): High performance HF receiver from 0.2 – 32 MHz
- FPGA based Wireless Processor, WPM3A, enables wideband signal processing.
- Timestamped wideband and narrowband data.
- 1PPS Sync Signal Input/Output.
- 10 MHz Reference Signal Input/Output.
- Built-in GPS receiver.
- Eight slots are available for any combination of tuners and WPM3As. A non-blocking switch routes the Digitized IF (DIF) Data from any slot to any other slot. Up to eight DIF channels into a WPM3A.
- Small size and low power.
- User-friendly Graphical User Interface (GUI).
- Supports target lists with up to 10,000 entries.
- Controlled from PC using *Windows XP* or *Windows 7* via Ethernet interface.
- 16 half-duplex conversations can be recorded on internal disk drive or other networked devices. E1 output optional. Stereo headphone output directly from receiver or headphone output can be streamed to a PC.
- Integrated spectrum analysis tool.
- Auto-configuration mode facilitates setup of unit.

Specifications

Total Number of Slots for Tuners and Wireless Processor Modules (WPM3As): 8

Maximum Number of Tuners: 8 (16 RF Channels)

Maximum Number of WPM3As: 8

Maximum Number of Channels:

Up to 336 (half-duplex)

Frequency Coverage (varies with type of tuners installed):

0.5 MHz – 3000 MHz (Standard, with RFT3)

0.5 MHz – 6500 MHz (Optional, with RFT4)

0.2 MHz – 32 MHz (Optional, with HFT1B)

Audio Outputs:

16-Channel Digital Recorder

Stereo Headphones

Streaming Data Service (SDS)

E1 Audio (Optional)

RIM (Optional)

IQ Data Streaming: Via SDS over TCP/IP

System Software:

DRT1000 System Software

Windows XP Operating System

Compatible with:

Controller PC running: *Windows XP* or *Windows 7*

Dimensions:

7.0" H x 13.0" W x 11.5" D

(17.8 cm H x 33.1 cm W x 29.3 cm D)

Dimensions do not include removable handles

Weight: Typical weight: 44.4 lbs. (18.42 kg)
(2 RFT3A-40s, 6 WPM3As)

Weight varies with the number and type of modules installed. Chassis with System Controller and Reference Generator modules weighs 28 lbs. (12.75 kg). See specific module data sheets for weights of additional modules.

Operating Temperature (Ambient):

-20°C to +60°C (-4°F to +140°F)

Power Consumption:

490 W – Fully loaded (2 RFT3s, 6 WPM3s)
 650 W – Max

Power Required:

100–240 VAC, 50-60 Hz; 110–130 VAC, 400 Hz; or 22-36 VDC, user selectable

Control Interface: Gigabit Ethernet

SRI Output Interfaces:

RS-232
 Ethernet
 E1 Timeslot (Optional)

Standard system ships with:

- Receiver with custom Tuner/WPM configuration
- User-friendly software with online help
- Integrated Spectral Display Unit (SDU)
- Ethernet crossover cable
- Stereo Headphones
- Omni-directional antenna with magnetic mount and coaxial cable
- REF3 GPS Antenna

Options:

- Fully configured Laptop PC (Office or Ruggedized Model) – including installed Ethernet card
- WLAN Control Interface
- Direction Finding (DF)

Drives:

- Zeroize capable and Non-Zeroize capable system drives are available in various sizes. Contact DRT for current list.
- Volatile Memory Option (VMO) Drive

Modules:

- CTL28 – System Controller Module
- GPPx – General Purpose Processor
- ES5P – Ethernet Switch 5 Port
- E1C 4-port - Audio Output Module
- DIM1B – Digital Interface Module for output/playback of wideband spectrum with external digital recorder
- RIM1C – Recorder Interface Module
- RFT4 - Wideband Tuner
- HFT1B - HF Tuner
- DEL1 - Delay Module
- 10GigE (Future)
- Quad Tuner (Future)

This page is intentionally blank.

Approved by DoD/OSR for public release under 14-S-2130 on 28 July 2014. Data, including specifications, contained within this document are summary in nature and subject to change without notice.

12409 Milestone Center Drive, Germantown, MD 20876-7114
Phone: 855-401-4185 ~ Fax: 301-916-5787 ~ www.drtd.com ~ international@drtd.com

Rev. 2.1-INT, September 2013
© Digital Receiver Technology, Inc., 2013