

BOOSTER DETONATOR

A BOOSTER DETONATOR IS USED TO SET OFF LARGE CHARGES OF 25-200 POUNDS AT A TIME. LARGER CHARGES SHOULD BE DETONATED BY USE OF A PRIMARY 5 POUND OR LARGER CHARGE PLACED IN THE CENTER OF THE TAP OF YOUR LARGE CHARGE, DRUMS ETC...

MATERIALS NEEDED TO MAKE ONE:

PICRIC ACID, HMTD, 30-06 OR 3030 EMPTY SHELL, WOOD DOWEL THAT FITS SNUG INTO THE SHELL HOLE, EPOXY, GREEN FUSE, EPOXY SPRAY PAINT.

1. FILL THE SHELL WITH EPOXY PAINT AND POUR IT OUT TO COAT THE INSIDE OF THE SHELL WITH PAINT AND LET IT DRY.
2. FILL THE SHELL HALF FULL WITH PICRIC ACID.
3. MAKE SURE YOU SLIGHTLY PRESS THE ACID IN WITH THE DOWEL.
4. FILL THE SHELL THE REMAINDER WITH THE HMTD AND PRESS INTO PLACE.
5. INSERT A FUSE AND CRIMP, SEAL WITH EPOXY.

THERE.

INFORMATION LABORATORIES OR ANY OF IT'S AFFILIATES ARE IN NO WAY RESPONSIBLE FOR THE USE OR MISUSE OF THIS OR ANY OTHER INFORMATION OBTAINED FROM INFO-LABS OR ANY OTHER SOURCE. DO NOT MAKE THIS MATERIAL.
